

Beam RST740 Iridium Active Antenna is a small, omni-directional antenna with a high quality enclosure. It is designed to work on Beam's Iridium docks and terminals. It comes complete with a power supply (15V DC output). It can support long cable runs of more than 100m (328 feet).

DC Peak Power Draw

SPECIFICATIONS

FEATURES			
Design	High quality enclosure		
	Active antenna		
	Pole/Mast mounting		
	TNC Antenna Input		
	White		
	Small size / footprint		
	Omni directional		
	Supports long cable runs		
SPECIFICATIONS			
Frequency	1616 MHz - 1626.5 MHz		
Temperature	-40°C to +70°C		
Input Voltage	9 - 36 VDC		
Dimensions without mounting bracket	143.8mm Height x 142.5mm Diameter	5.66" Height x 5.61" Diameter	
Weight	0.9 kg	1.98 lbs	

DC RMS Power Draw	3.2W		
DC RMS Standby Power Draw	320mW		
APPLICATIONS			
Luxury Vessels, Fishing Vessels & Recreational Boating			
Homesteads, Remote Farms & Buildings			
ACCESSORIES			
RST944 23m cable kit (Active) 5mm diameter			
RST945 34m cable kit (Active) 6mm diameter			
RST946 52m cable kit (Active) 10mm diameter			
SPECIAL ORDER ACCESSORIES			
RST947 75m cable kit (Active) 1 x 2 x	69m 15mm cable 3m 6mm fly leads.		
RST948 104m cable kit (Active) 1 x 2 x	90m 28mm cable 7m 6mm fly leads.		
NOTE: All cable kits include 1.5 m lead from dock/terminal to Antenna Amplifier. Warning: Use active cables only. Standard cables will damage the antenna.			

30W

www.beamcommunications.com



+61 3 8588 4500

+61 3 9560 9055



info@beamcommunications.com

RST740_REV02_08/12

AFRICA ASIA

AUSTRALIA

EUROPE

MIDDLE EAST

NORTH AMERICA

SOUTH AMERICA